

# ÆRATIS

( Æ r ' - u h - t i s )

PVC PORCH FLOORING

## **MATERIAL SAFETY DATA SHEET**

### **NAME OF PRODUCT Aeratis**

#### **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: Aeratis, composite porch board

MANUFACTURER: Building Products International, LLC

ADDRESS: PO Box 13554, Chandler, AZ 85248

Chemical Name: Composite mixture

EMERGENCY PHONE:

PRODUCT USE: Porch flooring

#### **SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name: Polyvinyl Chloride Compound

CAS NO. N/A

% WT: 50 – 85%

Chemical Name: Cellulose

CAS No: 9004-34-6

% WT: 10 – 25%

Chemical Name: Lubricant mixture

Calcium Stearate, CAS No.: 1592-23-0

Paraffin Wax, CAS No.: 8002-74-2

Polyethylene Wax, CAS No.: 68441-17-8

% WT: 0 – 5%

Chemical Name: Process Aids, Acrylic polymers

CAS No: Proprietary

% WT 0 – 3%

Chemical Name: Impact Modifiers, Acrylic

CAS No: Proprietary

% WT 0 – 10%

Chemical Name: Colorants  
Titanium Dioxide, CAS No: 13463-67-7  
Organic Pigments, CAS No: Proprietary  
Inorganic Pigments, CAS No: Proprietary

### **SECTION 3: HAZARDS IDENTIFICATION**

#### EMERGENCY OVERVIEW:

In normal use, the product is not hazardous. However, this product may be cut or finished in ways which produce dust by cutting or sawing. Use of a dust mask is recommended since certain fillers are considered hazardous if the airborne concentration exceeds the OSHA or ACGIH exposure limits for long periods of time. This amount of exposure is considered unlikely with this product due to all fillers in the product being fully stabilized in the plastic resin matrix. Dispose of waste as normal refuse.

### **SECTION 4: FIRST AID MEASURES**

EYES: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritations persist, seek medical attention.

SKIN: No known effects

INGESTION: Ingestion of this material is unlikely; however if it does occur, seek medical attention immediately.

INHALATION: This material is not expected to present an inhalation hazard. If having inhalation problems remove to fresh air and seek medical attention.

### **SECTION 5: FIRE-FIGHTING MEASURES**

FLASH POINT: N/A

AUTOIGNITION TEMPERATURE: N/A

#### NFPA HAZARD CLASSIFICATION

HEALTH: 0                      FLAMMABILITY: 1                      REACTIVITY: 0

EXTINGUISHING MEDIA: Water

SPECIAL FIRE FIGHTING PROCEDURES: Use water to keep fire exposed product cool. For fires in enclosed areas, fire fighters must use self-contained breathing apparatus.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### ACCIDENTAL RELEASE MEASURES:

Scoop up or vacuum material. Place in a suitable container for disposal in accordance with local, state or federal laws.

## **SECTION 7: HANDLING AND STORAGE**

HANDLING AND STORAGE: Do not use in applications where heavy structural loads must be supported or bracing is required, or directly adjacent to any high heat applications.

OTHER PRECAUTIONS: Do not burn in fireplace, burning barrel, or use as firewood.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

RESPIRATORY PROTECTION: Use in a well ventilated area. Provide ventilation to control nuisance dust levels to worker exposure limits. Use a properly fitting, approved dust respirator for dusty conditions or if breathing of dusts is likely.

EYE PROTECTION: Safety Glasses with side shields.

SKIN PROTECTION: Long sleeved clothing.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety shoes recommended.

WORK HYGIENIC PRACTICES: Handle in accordance with good industrial hygiene and safety practices.

EXPOSURE GUIDELINES:

Vinyl Chloride: 15 ppm PEL, TWA, Respirable, 15 min. OSHA

Total Dust: 15 mg/m<sup>3</sup>, TWA, OSHA

Total Dust: 10 mg/m<sup>3</sup>, TWA, ACGIH

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE: Profiles are various colors

ODOR: Faint

PHYSICAL STATE: Solid

BOILING POINT: N/A

MELTING POINT: 315° F

VAPOR PRESSURE: N/A

SPECIFIC GRAVITY: 1.1 – 1.3

## **SECTION 10: STABILITY AND REACTIVITY**

REACTIVITY: None

STABILITY: Stable

CORROSIVITY: None

INCOMPATIBILITY: None

REACTIVITY WITH WATER: None

EXPLOSION: Does not support rapid combustion, high dust levels may create potential for explosion

## **SECTION 11: TOXICOLOGICAL INFORMATION**

TOXICOLOGICAL INFORMATION:

Sawing, sanding and machining of this product may produce nuisance dust. See Section 8 for precautions.

## **SECTION 12: ECOLOGICAL INFORMATION**

ECOLOGICAL INFORMATION: Adverse ecological impact is not known or expected under normal use.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL METHOD: This finished product is not specifically listed by the EPA as a hazardous waste (40, part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. The generator of waste material has the responsibility for proper waste classification, and disposal in accordance with applicable local, state, and federal regulations.

## **SECTION 14: TRANSPORT INFORMATION**

Domestic transportation of these products are not defined or designated as a hazardous material by the USDOT under Title 49 of the Code of Federal Regulations, 1983 Edition.

## **SECTION 15: REGULATORY INFORMATION**

No EPA or OSHA requirements exist for this product. Members of Building Products International, LLC and its affiliates are not liable for information given herein.

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and we expressly disclaim all warranties of every kind and nature, including warranties of merchantability and fitness for particular purpose in respect to the use and suitability of the product. Nothing is intended as a recommendation for uses, which infringe valid patents, or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.